



| | |
|-------------------------------|-----------------------------------|
| Supplier's name or trade mark | AIRONE |
| Model identifier | CARMEN 90 con KIT MOTORE E1300 |

| | |
|--|-------|
| Annual Energy Consumption AEC (kWh/a) | 87.6 |
| Energy Efficiency Class | B |
| Fluid Dynamic Efficiency FDE (%) | 24.4 |
| Fluid Dynamic Efficiency class | B |
| Light Efficiency LE (lux/W) | 92.0 |
| Lighting Efficiency Class | A |
| Grease Filtering Efficiency GFE (%) | 30.4 |
| Grease Filtering Efficiency class | G |
| Minimum Air Flow in normal use (m ³ /h) | 365 |
| Maximum Air Flow in normal use (m ³ /h) | 593 |
| Air Flow at intensive/boost setting (m ³ /h) | 685 |
| A-weighted Sound Power Emission at minimum speed (dB(A)) | 59 |
| A-weighted Sound Power Emission at maximum speed (dB(A)) | 70 |
| A-weighted Sound Power Emission at intensive or boost speed (dB(A)) | 74 |
| Power consumption off mode PO (W) | 0.00 |
| Power consumption in standby mode PS (W) | 0.49 |
| Time increase factor | 1.1 |
| Energy Efficiency Index EEI | 69.1 |
| Measured air flow rate at best efficiency point QBEP (m ³ /h) | 349.2 |
| Measured air pressure at best efficiency point PBEP (Pa) | 463 |
| Maximum air flow DE Maximaler Luftstrom QMAX (m ³ /h) | 685.0 |
| Measured electric power input at best efficiency point WBEP (W) | 183.9 |
| Nominal power of the lighting system WL (W) | 18.9 |
| Average illumination of the lighting system on the cooking surface EMIDDLE (lux) | 1739 |