



| | |
|------------------|-----------------|
| Supplier's name | AIRONE |
| Model identifier | AIDA 60 + AMF13 |

| | |
|--|-------|
| Annual Energy Consumption AEC (kWh/a) | 72.0 |
| Energy Efficiency Class | B |
| Fluid Dynamic Efficiency FDE (%) | 24.6 |
| Fluid Dynamic Efficiency class | B |
| Light Efficiency LE (lux/W) | 49.7 |
| Lighting Efficiency Class | A |
| Grease Filtering Efficiency GFE (%) | 80.0 |
| Grease Filtering Efficiency class | C |
| minimum Air Flow in normal use (m ³ /h) | 335 |
| Maximum Air Flow in normal use (m ³ /h) | 533 |
| Air Flow at intensive/boost setting (m ³ /h) | 605 |
| A-weighted Sound Power Emission at minimum speed (dB(A)) | 57 |
| A-weighted Sound Power Emission at maximum speed (dB(A)) | 68 |
| A-weighted Sound Power Emission at intensive or boost speed (dB(A)) | 71 |
| Power consumption off mode PO (W) | 0.00 |
| Power consumption in standby mode PS (W) | 0.49 |
| Time increase factor | 1.1 |
| Energy Efficiency Index | 63.8 |
| Measured air flow rate at best efficiency point QBEP (m ³ /h) | 298.3 |
| Measured air pressure at best efficiency point PBEP (Pa) | 519 |
| Maximum air flow QMAX (m ³ /h) | 605.0 |
| Measured electric power input at best efficiency point WBEP (W) | 175.0 |
| Nominal power of the lighting system WL (W) | 2.4 |
| Average illumination of the lighting system on the cooking surface EMIDDLE (lux) | 119 |